

Identification_Information:

Citation:

Citation_Information:

Originator: EarthData International of Maryland, LLC
Publication_Date: 20020900
Publication_Time: Unknown
Title: Digital Land Base Mapping of the Town of Sevastopol, Door County, WI
Edition: 1st Edition
Geospatial_Data_Presentation_Form: map
Series_Information:
Publication_Information:
Larger_Work_Citation:
Citation_Information:
Series_Information:
Publication_Information:

Description:

Abstract:

This metadata document describes the collection and processing of Light Detection and Ranging (LIDAR) data of the Town of Sevastopol in Door County, Wisconsin. The resulting data are a bare ground elevation model generated from LIDAR data and topographic mapping with a 2' contour interval produced for the United States Army Corps of Engineers.

Purpose:

This dataset is intended for use by the United States Army Corps of Engineers for base mapping.

Time_Period_of_Content:

Time_Period_Information:

Single_Date/Time:
Calendar_Date: 20020900
Range_of_Dates/Times:
Multiple_Dates/Times:

Currentness_Reference: Publication Date

Status:

Progress: Complete
Maintenance_and_Update_Frequency: None planned

Spatial_Domain:

Bounding_Coordinates:

West_Bounding_Coordinate: -087.410728
East_Bounding_Coordinate: -087.150754
North_Bounding_Coordinate: 44.949903
South_Bounding_Coordinate: 44.840827

Keywords:

Theme:

Theme_Keyword_Thesaurus: None
Theme_Keyword: Digital Land Base Mapping
Theme_Keyword: Light Detection and Ranging (LIDAR)
Theme_Keyword: Topographic Map

Place:

Place_Keyword_Thesaurus: None
Place_Keyword: United States of America (USA)
Place_Keyword: Wisconsin (WI)
Place_Keyword: Door County (55029)
Place_Keyword: Town of Sevastopol

Stratum:

Temporal:

Access_Constraints: None

Use_Constraints: None

Point_of_Contact:

Contact_Information:

Contact_Person_Primary:

Contact_Organization_Primary:

Contact_Organization: EarthData International of Maryland

Contact_Address:

Address_Type: mailing and physical address

Address: 45 West Watkins Mill Rd

City: Gaithersburg

State_or_Province: MD

Postal_Code: 20878

Country: USA

Contact_Voice_Telephone: 301-948-8550

Contact_Facsimile_Telephone: 301-963-2064

Contact_Electronic_Mail_Address: metadata@earthdata.com

Hours_of_Service: 9:00-5:00 M-F

Security_Information:

Cross_Reference:

Citation_Information:

Series_Information:

Publication_Information:

Data_Quality_Information:

Attribute_Accuracy:

Logical_Consistency_Report:

Height values between individual LIDAR points within a 3.5 meter radius were differentiated against surveyed control points. A statistical result was determined and indicated that the vertical RMSE was +/- 0.15 meters (1 sigma) over the project area.

The resultant map products are fully compliant with National Map Accuracy Standards.

Completeness_Report:

Differences between individual LIDAR points within a 3.5 meter radius were calculated against surveyed control points. A statistical result was determined and indicated that the vertical RMSE was +/- 0.15 meters (1 sigma) for the entire project.

The following software was used for the validation.

1. Bentley - Microstation
2. Terrasolid - Terrscan
3. Trimble - Terramodel
4. Esri - ArcInfo
5. EarthData Proprietary software

Positional_Accuracy:

Horizontal_Positional_Accuracy:

Vertical_Positional_Accuracy:

Lineage:

Source_Information:

Source_Citation:

Citation_Information:

Originator: Towill

Publication_Date: 20020400

Publication_Time: Unknown

Title: Ground Control Survey of Door County, WI

Geospatial_Data_Presentation_Form: model

Series_Information:

Publication_Information:

Publication_Place: Towill, Inc, San Francisco, CA

Publisher: Towill

Larger_Work_Citation:
 Citation_Information:
 Series_Information:
 Publication_Information:
 Source_Scale_Denominator: 14,400
 Type_of_Source_Media: electronic mail system
 Source_Time_Period_of_Content:
 Time_Period_Information:
 Single_Date/Time:
 Calendar_Date: 20020400
 Range_of_Dates/Times:
 Multiple_Dates/Times:
 Source_Currentness_Reference: Publication Date
 Source_Citation_Abbreviation: GPS Ground Control
 Source_Contribution:
 Ground control was established prior to the acquisition of
 aerial data acquisition. The ground control points were
 established using GPS for vertical and horizontal
 coordinate values. Ground control references the
 Wisconsin Central State Plane NAD83, NAVD29, US
 Survey Feet.
 Source_Information:
 Source_Citation:
 Citation_Information:
 Originator: EarthData Aviation
 Publication_Date: 20020417
 Publication_Time: Unknown
 Title: LIDAR Coverage of Door County, WI
 Geospatial_Data_Presentation_Form: model
 Series_Information:
 Publication_Information:
 Publication_Place: Hagerstown, MD
 Publisher: EarthData Aviation
 Larger_Work_Citation:
 Citation_Information:
 Series_Information:
 Publication_Information:
 Type_of_Source_Media: CD-ROM
 Source_Time_Period_of_Content:
 Time_Period_Information:
 Single_Date/Time:
 Calendar_Date: 20020300
 Time_of_Day: Unknown
 Range_of_Dates/Times:
 Multiple_Dates/Times:
 Source_Currentness_Reference: Publication Date
 Source_Citation_Abbreviation: Earthdata Aviation
 Source_Contribution:
 The project area was flown using EarthData Aviation's
 Navajo Chieftain aircraft equipped with an AeroScan
 LIDAR system, an Inertial Measurement Unit (IMU), and
 dual frequency GPS receiver and antennae. The position
 and orientation (omega, phi, and kappa) of the aircraft were
 determined using a GPS receiver located at an existing
 NGS control point.
 The LIDAR, IMU, and GPS data were correlated using
 GPS time and processed using LIDAR post-processing
 software to determine the coordinate of each point on the
 ground. A reflective surface DEM of the project area

was delivered with a relative accuracy of +/- 0.15 meters.

Process_Step:

Process_Description:

EarthData has developed a unique method for processing LIDAR data to identify and remove elevation points falling on vegetation, buildings, and other above-ground structures. The algorithms for filtering data were utilized within EarthData's proprietary software and commercial software written by TerraSolid. This software suite of tools provides efficient processing for small to large-scale projects and has been incorporated into ISO 9001 compliant production work flows. The following is a step-by-step breakdown of the process.

1. Using the LIDAR data set provided by EarthData Aviation, the technician performed a visual inspection of the data to verify that the flight lines overlap correctly. The technician also verified that there were no voids, and that the data covered the project limits. The technician then selected a series of areas from the dataset and inspected them where adjacent flight lines overlapped. These overlapping areas were merged and a process which utilizes 3-D Analyst and EarthData's proprietary software was run to detect and color code the differences in elevation values and profiles. The technician reviewed these plots and located the areas that contained systematic errors or distortions that were introduced by the LIDAR sensor.
2. Systematic distortions highlighted in step 1 were removed and the data were re-inspected. Corrections and adjustments can involve the application of angular deflection or compensation for curvature of the ground surface that can be introduced by crossing from one type of land cover to another.
3. The LIDAR data for each flight line were trimmed in batch for the removal of the overlap areas between flight lines. The data were checked against a control network to ensure that vertical requirements were maintained. Conversion to the client-specified datum and projections were then completed. The LIDAR flight line data sets were then segmented into adjoining tiles for batch processing and data management.
4. The initial batch-processing run removed 95% of points falling on vegetation. The algorithm also removed the points that fell on the edge of hard features such as structures, elevated roadways and bridges. In addition, points not classified as ground are coded as intermediate canopy, top of canopy, building, etc. Thus the LIDAR data was classified into thematic layers that can be analyzed separately or together.
5. The data were processed interactively by the operator using LIDAR editing tools. During this final phase the operator generated a TIN based on a desired thematic layers to evaluate the automated classification performed in step 4. This allowed the operator to quickly re-classify points from one layer to another and recreate the TIN surface to see the effects of edits. The use of geo-referenced images were toggled on or off to aid the operator in identifying problem areas. The data was also examined with an automated profiling tool to aid the

operator in the reclassification.

6.The data were separated into a bare-earth DEM. A grid fill program was used to fill data voids caused from reflective objects such as buildings and vegetation. The final DEM was written as an ASCII file (comma & space delimited), ESRI Shape file, and an ESRI TIN file to a CDROM.

Source_Used_Citation_Abbreviation: EarthData International

Process_Date: 20020900

Process_Contact:

Contact_Information:

Contact_Person_Primary:

Contact_Person: Raquel Charrois

Contact_Organization: EarthData International

Contact_Organization_Primary:

Contact_Address:

Address_Type: mailing and physical address

Address: 45 West Walkins Mill Road

City: Gaithersburg

State_or_Province: Maryland

Postal_Code: 20878

Country: USA

Contact_Voice_Telephone: 1-301-948-8550

Contact_Facsimile_Telephone: 1-301-963-2064

Contact_Electronic_Mail_Address: international-md@earthdata.com

Hours_of_Service: 9 AM - 5 PM Mon. - Fri.

Cloud_Cover: 0

Spatial_Data_Organization_Information:

Spatial_Reference_Information:

Horizontal_Coordinate_System_Definition:

Planar:

Grid_Coordinate_System:

Grid_Coordinate_System_Name: State Plane Coordinate System 1983

Universal_Transverse_Mercator:

Transverse_Mercator:

Universal_Polar_Stereographic:

Polar_Stereographic:

State_Plane_Coordinate_System:

SPCS_Zone_Identifier: Wisconsin Central (4802)

Lambert_Conformal_Conic:

Standard_Parallel: 44 15 0.0

Standard_Parallel: 45 30 0.0

Longitude_of_Central_Meridian: -090.000000

Latitude_of_Projection_Origin: +43.833333

False_Easting: 600000.0

False_Northing: 0.0

Transverse_Mercator:

Oblique_Mercator:

Oblique_Line_Point:

Polyconic:

ARC_Coordinate_System:

Equiarectangular:

Azimuthal_Equidistant:

Planar_Coordinate_Information:

Planar_Coordinate_Encoding_Method: coordinate pair

Coordinate_Representation:

Abscissa_Resolution: 2

Ordinate_Resolution: 2

Distance_and_Bearing_Representation:

Planar_Distance_Units: Survey Feet
 Geodetic_Model:
 Vertical_Coordinate_System_Definition:
 Altitude_System_Definition:
 Altitude_Datum_Name: National Geodetic Vertical Datum of 1929
 Altitude_Resolution: 0.15
 Altitude_Distance_Units: Meters
 Altitude_Encoding_Method: Explicit elevation coordinate included with horizontal coordinates
 Depth_System_Definition:
 Entity_and_Attribute_Information:
 Detailed_Description:
 Entity_Type:
 Attribute:
 Attribute_Domain_Values:
 Attribute_Value_Accuracy_Information:
 Overview_Description:
 Distribution_Information:
 Distributor:
 Contact_Information:
 Contact_Person_Primary:
 Contact_Organization_Primary:
 Contact_Organization: United States Army Corps of Engineers - Detroit District
 Contact_Address:
 Address_Type: mailing and physical address
 Address: 477 Michigan Avenue
 City: Detroit
 State_or_Province: MI
 Postal_Code: 48226
 Country: USA
 Contact_Voice_Telephone: 313-226-6751
 Distribution_Liability: None.
 Standard_Order_Process:
 Digital_Form:
 Digital_Transfer_Information:
 Digital_Transfer_Option:
 Online_Option:
 Computer_Contact_Information:
 Network_Address:
 Dialup_Instructions:
 OffLine_Option:
 Recording_Capacity:
 Available_Time_Period:
 Time_Period_Information:
 Single_Date/Time:
 Range_of_Dates/Times:
 Multiple_Dates/Times:
 Metadata_Reference_Information:
 Metadata_Date: 20021000
 Metadata_Contact:
 Contact_Information:
 Contact_Person_Primary:
 Contact_Organization_Primary:
 Contact_Organization: EarthData International of Maryland, LLC
 Contact_Address:
 Address_Type: mailing and physical address
 Address: 45 West Watkins Mill Road
 City: Gaithersburg
 State_or_Province: MD
 Postal_Code: 20878

Country: USA

Contact_Voice_Telephone: 301-948-8550

Contact_Facsimile_Telephone: 301-963-2064

Contact_Electronic_Mail_Address: metadata@earthdata.com

Hours_of_Service: 9:00 AM - 5:00 PM (ET) M-F

Metadata_Standard_Name: FGDC Content Standards for Digital Geospatial Metadata

Metadata_Standard_Version: FGDC-STD-001-1998

Metadata_Security_Information: