

Identification\_Information:

Citation:

Citation\_Information:

Originator: EarthData International of Maryland, LLC  
 Publication\_Date: 20020900  
 Publication\_Time: Unknown  
 Title: Digital Land Base Mapping of the Town of Sturgeon Bay, Door County, WI  
 Edition: 1st Edition  
 Geospatial\_Data\_Presentation\_Form: map  
 Series\_Information:  
 Publication\_Information:  
 Larger\_Work\_Citation:  
 Citation\_Information:  
 Series\_Information:  
 Publication\_Information:

Description:

Abstract:

This metadata document describes the collection and processing of Light Detection and Ranging (LIDAR) data of the Town of Sturgeon Bay in Door County, Wisconsin. The resulting data are a bare ground elevation model generated from LIDAR data and topographic mapping with a 2' contour interval produced for the United States Army Corps of Engineers.

Purpose:

This dataset is intended for use by the United States Army Corps of Engineers for base mapping.

Time\_Period\_of\_Content:

Time\_Period\_Information:

Single\_Date/Time:  
 Calendar\_Date: 20020900  
 Range\_of\_Dates/Times:  
 Multiple\_Dates/Times:

Currentness\_Reference: Publication Date

Status:

Progress: Complete  
 Maintenance\_and\_Update\_Frequency: None planned

Spatial\_Domain:

Bounding\_Coordinates:

West\_Bounding\_Coordinate: -087.414410  
 East\_Bounding\_Coordinate: -087.248114  
 North\_Bounding\_Coordinate: 44.853488  
 South\_Bounding\_Coordinate: 44.758580

Keywords:

Theme:

Theme\_Keyword\_Thesaurus: None  
 Theme\_Keyword: Digital Land Base Mapping  
 Theme\_Keyword: Light Detection and Ranging (LIDAR)  
 Theme\_Keyword: Topographic Map

Place:

Place\_Keyword\_Thesaurus: None  
 Place\_Keyword: United States of America (USA)  
 Place\_Keyword: Wisconsin (WI)  
 Place\_Keyword: Door County (55029)  
 Place\_Keyword: Town of Sturgeon Bay

Stratum:

Temporal:

Access\_Constraints: None

Use\_Constraints: None

## Point\_of\_Contact:

## Contact\_Information:

Contact\_Person\_Primary:

Contact\_Organization\_Primary:

Contact\_Organization: EarthData International of Maryland

## Contact\_Address:

Address\_Type: mailing and physical address

Address: 45 West Watkins Mill Rd

City: Gaithersburg

State\_or\_Province: MD

Postal\_Code: 20878

Country: USA

Contact\_Voice\_Telephone: 301-948-8550

Contact\_Facsimile\_Telephone: 301-963-2064

Contact\_Electronic\_Mail\_Address: metadata@earthdata.com

Hours\_of\_Service: 9:00-5:00 M-F

## Security\_Information:

## Cross\_Reference:

## Citation\_Information:

Series\_Information:

Publication\_Information:

## Data\_Quality\_Information:

## Attribute\_Accuracy:

## Logical\_Consistency\_Report:

Height values between individual LIDAR points within a 3.5 meter radius were differentiated against surveyed control points. A statistical result was determined and indicated that the vertical RMSE was +/- 0.15 meters (1 sigma) over the project area.

The resultant map products are fully compliant with National Map Accuracy Standards.

## Completeness\_Report:

Differences between individual LIDAR points within a 3.5 meter radius were calculated against surveyed control points. A statistical result was determined and indicated that the vertical RMSE was +/- 0.15 meters (1 sigma) for the entire project.

The following software was used for the validation.

1. Bentley - Microstation
2. Terrasolid - Terrscan
3. Trimble - Terramodel
4. Esri - ArcInfo
5. EarthData Proprietary software

## Positional\_Accuracy:

Horizontal\_Positional\_Accuracy:

Vertical\_Positional\_Accuracy:

## Lineage:

## Source\_Information:

## Source\_Citation:

## Citation\_Information:

Originator: Towill

Publication\_Date: 20020400

Publication\_Time: Unknown

Title: Ground Control Survey of Door County, WI

Geospatial\_Data\_Presentation\_Form: model

Series\_Information:

Publication\_Information:

Publication\_Place: Towill, Inc, San Francisco, CA

Publisher: Towill

Larger\_Work\_Citation:  
     Citation\_Information:  
         Series\_Information:  
         Publication\_Information:  
 Source\_Scale\_Denominator: 14,400  
 Type\_of\_Source\_Media: electronic mail system  
 Source\_Time\_Period\_of\_Content:  
     Time\_Period\_Information:  
         Single\_Date/Time:  
             Calendar\_Date: 20020400  
         Range\_of\_Dates/Times:  
         Multiple\_Dates/Times:  
     Source\_Currentness\_Reference: Publication Date  
 Source\_Citation\_Abbreviation: GPS Ground Control  
 Source\_Contribution:  
     Ground control was established prior to the acquisition of  
     aerial data acquisition. The ground control points were  
     established using GPS for vertical and horizontal  
     coordinate values. Ground control references the  
     Wisconsin Central State Plane NAD83, NAVD29, US  
     Survey Feet.

Source\_Information:  
     Source\_Citation:  
         Citation\_Information:  
             Originator: EarthData Aviation  
             Publication\_Date: 20020417  
             Publication\_Time: Unknown  
             Title: LIDAR Coverage of Door County, WI  
             Geospatial\_Data\_Presentation\_Form: model  
             Series\_Information:  
                 Publication\_Information:  
                     Publication\_Place: Hagerstown, MD  
                     Publisher: EarthData Aviation  
             Larger\_Work\_Citation:  
                 Citation\_Information:  
                     Series\_Information:  
                     Publication\_Information:  
             Type\_of\_Source\_Media: CD-ROM  
             Source\_Time\_Period\_of\_Content:  
                 Time\_Period\_Information:  
                     Single\_Date/Time:  
                         Calendar\_Date: 20020300  
                         Time\_of\_Day: Unknown  
                 Range\_of\_Dates/Times:  
                 Multiple\_Dates/Times:  
             Source\_Currentness\_Reference: Publication Date  
             Source\_Citation\_Abbreviation: Earthdata Aviation  
             Source\_Contribution:  
                 The project area was flown using EarthData Aviation's  
                 Navajo Chieftain aircraft equipped with an AeroScan  
                 LIDAR system, an Inertial Measurement Unit (IMU), and  
                 dual frequency GPS receiver and antennae. The position  
                 and orientation (omega, phi, and kappa) of the aircraft were  
                 determined using a GPS receiver located at an existing  
                 NGS control point.  
                 The LIDAR, IMU, and GPS data were correlated using  
                 GPS time and processed using LIDAR post-processing  
                 software to determine the coordinate of each point on the  
                 ground. A reflective surface DEM of the project area

was delivered with a relative accuracy of +/- 0.15 meters.

Process\_Step:

Process\_Description:

EarthData has developed a unique method for processing LIDAR data to identify and remove elevation points falling on vegetation, buildings, and other above-ground structures. The algorithms for filtering data were utilized within EarthData's proprietary software and commercial software written by TerraSolid. This software suite of tools provides efficient processing for small to large-scale projects and has been incorporated into ISO 9001 compliant production work flows. The following is a step-by-step breakdown of the process.

1. Using the LIDAR data set provided by EarthData Aviation, the technician performed a visual inspection of the data to verify that the flight lines overlap correctly. The technician also verified that there were no voids, and that the data covered the project limits. The technician then selected a series of areas from the dataset and inspected them where adjacent flight lines overlapped. These overlapping areas were merged and a process which utilizes 3-D Analyst and EarthData's proprietary software was run to detect and color code the differences in elevation values and profiles. The technician reviewed these plots and located the areas that contained systematic errors or distortions that were introduced by the LIDAR sensor.

2. Systematic distortions highlighted in step 1 were removed and the data were re-inspected. Corrections and adjustments can involve the application of angular deflection or compensation for curvature of the ground surface that can be introduced by crossing from one type of land cover to another.

3. The LIDAR data for each flight line were trimmed in batch for the removal of the overlap areas between flight lines. The data were checked against a control network to ensure that vertical requirements were maintained. Conversion to the client-specified datum and projections were then completed. The LIDAR flight line data sets were then segmented into adjoining tiles for batch processing and data management.

4. The initial batch-processing run removed 95% of points falling on vegetation. The algorithm also removed the points that fell on the edge of hard features such as structures, elevated roadways and bridges. In addition, points not classified as ground are coded as intermediate canopy, top of canopy, building, etc. Thus the LIDAR data was classified into thematic layers that can be analyzed separately or together.

5. The data were processed interactively by the operator using LIDAR editing tools. During this final phase the operator generated a TIN based on a desired thematic layers to evaluate the automated classification performed in step 4. This allowed the operator to quickly re-classify points from one layer to another and recreate the TIN surface to see the effects of edits. The use of geo-referenced images were toggled on or off to aid the operator in identifying problem areas. The data was also examined with an automated profiling tool to aid the

operator in the reclassification.

6.The data were separated into a bare-earth DEM. A grid fill program was used to fill data voids caused from reflective objects such as buildings and vegetation. The final DEM was written as an ASCII file (comma & space delimited), ESRI Shape file, and an ESRI TIN file to a CDROM.

Source\_Used\_Citation\_Abbreviation: EarthData International

Process\_Date: 20020900

Process\_Contact:

Contact\_Information:

Contact\_Person\_Primary:

Contact\_Person: Raquel Charrois

Contact\_Organization: EarthData International

Contact\_Organization\_Primary:

Contact\_Address:

Address\_Type: mailing and physical address

Address: 45 West Walkins Mill Road

City: Gaithersburg

State\_or\_Province: Maryland

Postal\_Code: 20878

Country: USA

Contact\_Voice\_Telephone: 1-301-948-8550

Contact\_Facsimile\_Telephone: 1-301-963-2064

Contact\_Electronic\_Mail\_Address: international-md@earthdata.com

Hours\_of\_Service: 9 AM - 5 PM Mon. - Fri.

Cloud\_Cover: 0

Spatial\_Data\_Organization\_Information:

Spatial\_Reference\_Information:

Horizontal\_Coordinate\_System\_Definition:

Planar:

Grid\_Coordinate\_System:

Grid\_Coordinate\_System\_Name: State Plane Coordinate System 1983

Universal\_Transverse\_Mercator:

Transverse\_Mercator:

Universal\_Polar\_Stereographic:

Polar\_Stereographic:

State\_Plane\_Coordinate\_System:

SPCS\_Zone\_Identifier: Wisconsin Central (4802)

Lambert\_Conformal\_Conic:

Standard\_Parallel: 44 15 0.0

Standard\_Parallel: 45 30 0.0

Longitude\_of\_Central\_Meridian: -090.000000

Latitude\_of\_Projection\_Origin: +43.833333

False\_Easting: 600000.0

False\_Northing: 0.0

Transverse\_Mercator:

Oblique\_Mercator:

Oblique\_Line\_Point:

Polyconic:

ARC\_Coordinate\_System:

Equirectangular:

Azimuthal\_Equidistant:

Planar\_Coordinate\_Information:

Planar\_Coordinate\_Encoding\_Method: coordinate pair

Coordinate\_Representation:

Abscissa\_Resolution: 2

Ordinate\_Resolution: 2

Distance\_and\_Bearing\_Representation:

Planar\_Distance\_Units: Survey Feet

Geodetic\_Model:

Vertical\_Coordinate\_System\_Definition:

Altitude\_System\_Definition:

Altitude\_Datum\_Name: National Geodetic Vertical Datum of 1929

Altitude\_Resolution: 0.15

Altitude\_Distance\_Units: Meters

Altitude\_Encoding\_Method: Explicit elevation coordinate included with horizontal coordinates

Depth\_System\_Definition:

Entity\_and\_Attribute\_Information:

Detailed\_Description:

Entity\_Type:

Attribute:

Attribute\_Domain\_Values:

Attribute\_Value\_Accuracy\_Information:

Overview\_Description:

Distribution\_Information:

Distributor:

Contact\_Information:

Contact\_Person\_Primary:

Contact\_Organization\_Primary:

Contact\_Organization: United States Army Corps of Engineers - Detroit District

Contact\_Address:

Address\_Type: mailing and physical address

Address: 477 Michigan Avenue

City: Detroit

State\_or\_Province: MI

Postal\_Code: 48226

Country: USA

Contact\_Voice\_Telephone: 313-226-6751

Distribution\_Liability: None.

Standard\_Order\_Process:

Digital\_Form:

Digital\_Transfer\_Information:

Digital\_Transfer\_Option:

Online\_Option:

Computer\_Contact\_Information:

Network\_Address:

Dialup\_Instructions:

OffLine\_Option:

Recording\_Capacity:

Available\_Time\_Period:

Time\_Period\_Information:

Single\_Date/Time:

Range\_of\_Dates/Times:

Multiple\_Dates/Times:

Metadata\_Reference\_Information:

Metadata\_Date: 20021000

Metadata\_Contact:

Contact\_Information:

Contact\_Person\_Primary:

Contact\_Organization\_Primary:

Contact\_Organization: EarthData International of Maryland, LLC

Contact\_Address:

Address\_Type: mailing and physical address

Address: 45 West Watkins Mill Road

City: Gaithersburg

State\_or\_Province: MD

Postal\_Code: 20878

Country: USA

Contact\_Voice\_Telephone: 301-948-8550

Contact\_Facsimile\_Telephone: 301-963-2064

Contact\_Electronic\_Mail\_Address: metadata@earthdata.com

Hours\_of\_Service: 9:00 AM - 5:00 PM (ET) M-F

Metadata\_Standard\_Name: FGDC Content Standards for Digital Geospatial Metadata

Metadata\_Standard\_Version: FGDC-STD-001-1998

Metadata\_Security\_Information: